

SCA CHEMICAL SERVICES, INC.

AN SCA SERVICES COMPANY

11700 S. Stony Island Avenue
Chicago, Illinois 60617
(312) 546-5700

EPA Region 5 Records Ctr.



351299



July 27, 1983

Mr. Howard Chinn
Chief Engineer
Environmental Control Division
State of Illinois
Attorney General's Office
160 North LaSalle Street
Chicago, Illinois 60601

Subject: Disposal of "Cyanide Chips"

Dear Mr. Chinn:

Per your recent discussion with SCA's George Kush, Director of Environmental Affairs, I am forwarding Laboratory Data covering recent thermal destruction of a cyanide bearing waste at SCA's South Chicago incinerator. We routinely destruct various cyanide contaminated sludges such as TDI (Toluene Di Isocyanate) in our kiln at 1600° to 1800°F and cyanide contaminated liquids in our secondary combustion chamber at temperatures in excess of 2000°F.

Since the cyanide complex totally breaks down at temperatures in excess of 1000°F, there is absolutely no possibility of cyanide emissions from our operations. However, as substantiation of this, we submit the attached analysis of our scrubbing tower water following destruction of a recent cyanide bearing waste with concentration far in excess of that present in the cyanide chips. Dr. Richard Carnes, Director of the USEPA Research Facility at Pine Bluff, Arkansas would also be happy to confirm that cyanide bearing waste can be efficiently and totally disposed of via thermal destruction in a high technology incinerator.

We feel that SCA can offer the most environmentally secure method of disposal at economics comparable to current alternatives. Disposal price for the "chips" would be \$0.10/lb. packaged in incinerable containers. If repacking at our plant is required, our price would be \$0.12/lb.

As a full service company with expertise in all phases of Hazardous Waste Disposal, SCA would be happy to inspect the locations where the remaining cyanide chips are stored and provide consultation on the most appropriate means of transferring to our incinerator. Also, we would like to extend an invitation to you and any other member of the Attorney General's staff to inspect our Facility.

SCA CHEMICAL SERVICES, INC.



Mr. Howard Chinn
Chief Engineer
Environmental Control Division
State of Illinois
Attorney General's Office
July 27, 1983
Page 2

If you have any questions on the above, please feel free to contact me at 11700 South Stony Island Avenue, Chicago, Illinois or phone (312) 646-5700.

Sincerely,

A handwritten signature in dark ink, appearing to read "Clark J. Rose", is written over a horizontal line.

Clark J. Rose
Vice President

CJR/dc

attachment




Cyanide Test Burn

July 26, 1983

On July 8, 1983 and July 9, 1983, a waste stream found to contain 2.13% total cyanide was incinerated. Water samples of the MSD discharge, prescrubber and retention tank and air sampling of the retention tank vent was performed by operations personnel during the incineration.

Analysis of samples by the laboratory showed no abnormal cyanide concentrations in the incinerator process.

Please find attached copies of the laboratory data.


Gregory E. Pronger
Laboratory Manager

GEP/dc

cc: Clark Rose
John Valerius
Alicia Whatley
George Kush
Dick Moon
Ken Anderson
Gerry Piper

attachments

Cyanide 7/8/83

Time	MSD (PPM)	RTK (PPM)	PRE (PPM)
9:00 PM	<0.2	<0.02	<0.02
9:30 PM	<0.2	<0.02	<0.02
10:00 PM	<0.2	<0.02	<0.02
10:30 PM	<0.2	<0.02	<0.02
11:00 PM	<0.2	<0.02	<0.02
11:30 PM	<0.2	<0.02	<0.02
12:00 AM	<0.2	<0.02	<0.02
12:30 AM	<0.2	<0.02	<0.02
1:00 AM	<0.2	<0.02	<0.02
1:30 AM	<0.2	<0.02	<0.02
2:00 AM	<0.2	<0.02	<0.02

Bubbler	CN (PPM)
#1	<0.2
#2	<0.2
#3	<0.2

Sample of Waste Incinerated - Total 2.13% cyanide

Flow rate on vacuum pump

$$7.5 \text{ sec./100ml}$$

$$\frac{100\text{ml}}{7.5 \text{ sec./60 sec./min.}} = 800\text{ml/min.} = 0.8 \text{ liters/min.}$$

Molar volume of Ideal Gas

$$V_m = RT_0/P_0$$

$$R = 8.206 \times 10^{-2} \text{ m}^3 \text{ atm mole}^{-1} \text{ K}^{-1}$$

$$T_0 = 302^\circ\text{K} (85^\circ\text{F})$$

$$P_0 = 1 \text{ atm}$$

$$V_m = \frac{8.206 \times 10^{-6} (302)}{1} = 24.8 \frac{\text{liters}}{\text{mole}}$$

Molar weight of air \approx 28.9g/mole

$$\text{Weight of air through pump} = \frac{28.9\text{g/mole}}{24.8 \text{ liter/mole}} \times 0.8 \text{ liter/min.} = 0.93\text{g/min.}$$

Cyanide in air first scrubber:

pump run 79 minutes

79 minutes x 0.93g/min. = 73g air

<0.1PPM CN^-

$$<0.1 \text{ mg/l} \times 100\text{ml} \times \frac{1\text{L}}{1000\text{ml}} \times \frac{1000\text{ug}}{\text{mg}} = <10\text{ug } \text{CN}^-$$

$$\frac{<10\text{ug } \text{CN}^-}{73\text{g air}} = <0.14\text{PPM } \text{CN}^- \text{ in air}$$